

FILTERS, CONVERTERS & GSM-PRO CONTROLLERS

LINE FILTERS



IF-OF/0.5A	Single Phase 230V Line Filter for general use - 0.5 Amp	\$138.13
IF-OF/1A	Single Phase 230V Line Filter for general use - 1 Amp	\$138.13
IF-OF/3A	Single Phase 230V Line Filter for general use - 3 Amp	\$150.40
IF-OF/6A	Single Phase 230V Line Filter for general use - 6 Amp	\$176.49

SIGNAL CONVERTERS



CML-PT100-UI (-50/+50°C)	Signal Converter PT100 to 0/10V or 4-20mA Output	\$367.39
CML-PT100-UI (0/+100°C)	Signal Converter PT100 to 0/10V or 4-20mA Output	\$367.39
CML-PT100-UI (0/+200°C)	Signal Converter PT100 to 0/10V or 4-20mA Output	\$367.39
CML-PT100-UI (0/+300°C)	Signal Converter PT100 to 0/10V or 4-20mA Output	\$367.39
CML-PT100-UI (0/+400°C)	Signal Converter PT100 to 0/10V or 4-20mA Output	\$367.39
CML-UI-UI	Signal Converter 0/10V or 4-20mA to 0/10V or 4-20mA Output	\$367.39
CML-POT-UI	Signal Converter 1 to 20kΩ to 0/10V or 4-20mA Output	\$367.39

GSM-PRO CONTROLLER

Conta-Clip's GSM PRO module provides a solution for remotely monitoring and controlling processes by means of SMS signals, emails & GPRS.

Status messages are able to be sent over the GSM network if a process has reached a specified level. The digital and analog input values can also be transmitted via SMS text message. If the values indicate a critical status, the GSM-PRO device gives the service technician the option to control the analogue and digital outputs by SMS. This enables him to take action immediately without being constantly on-site. The module can be used stand alone, but can also be used as a remote module in your control system. The accompanying software can be used to easily set the parameters for the inputs and outputs.

The GSM-PRO Controller can be used whenever the status of process parameters must be monitored. Several application possibilities include: Wind Power Sites, Pump and Irrigation, Poultry Farms, monitoring of remote unmanned sites and level monitoring.



GSM-PRO2	GSM Controller with 2 Multifunction Inputs and 1 Relay Output	\$1,120.22
GSM-PRO2E	GSM Controller with 10 Multifunction Inputs and 4 Relay Outputs	\$1,569.93
GSM-PRO2DO	Digital Output Module - 4 Digital Outputs	\$544.55
GSM-PRO2AI	Analogue Input Module - 8 Multifunction Analogue Inputs	\$597.46
GSM-Antenna	Standard internal antenna	\$34.69
GSM-Antenna-90	GSM-Pro2 External Antenna-90 Degree	\$56.02
GSM-Antenna-SMA	GSM-Pro2 External Antenna-3m Lead	\$376.11
GSM-Antenna-SMA-EC	GSM-Pro2 External Antenna-3m Lead	\$175.84
GSM-USB Cable	USB programming cable	\$23.03